User Manual_

C2 KA

Outdoor RFID Access Control Terminal

Safety Instructions

Read carefully these instructions carefully before using product in strictly present mode to prevent others and present personal injuries and property damage caused by incorrect installation or the improper use of this product.

- Control mount device the product attentively. You may wind in injuries if product falls during installation.
- Do not disassemble product by yourself(otherwise the certificate/warranty will be void).
- Do not place product near heat source(such as radiator, heater, stove, or gas tank. This may result in electric shock or fire.
- The operating environment of C2KA is limited at -40°C~+60°C(-40°F~140°F) and humidity 20~80%. Do not place product at -40°C(-40°F) and humidity 20~80%.
- Do not use dangerous or unacceptable chemicals, sprays, or flows and local cleaners. Chemicals(such as, toluene, xylene, acetone and ethyl ether) can damage product power supply and C2 KA terminal. DC 12V ~ 3A.
- Clean dirt or cleaner particles the product. The product may malfunction.
- When cleaning the product, wipe it with lint-free and dry towel.
- Do not place product near the electric or electronic devices. Product may malfunction or cause other electronic or electronic devices to malfunction. Keep product at least 30cm away from other electronic or electronic devices.
- Do not attempt to disassemble the outer of the product.
- Do not use product for anything other than intended use.

Introduction

Front view

Appearance Description


Lower Shell
Mounting Plate
Screw Hole
Screw Hole
Screw Hole